

MQTT API

The screenshot shows the 'Zigbee Hub MQTT integration settings' interface. It features a dark theme with a top bar containing the title and a help icon. Below the title, there is a toggle switch for 'Enable MQTT' which is turned on. The settings are organized into sections: 'MQTT broker host' (192.168.50.165), 'MQTT broker port' (1883), 'Username' (mqtt), 'Password' (masked with dots), and 'Base topic' (zhub). Each input field has a green checkmark on the right. A second section is for 'Home Assistant MQTT Discovery', with a toggle switch turned on and a 'Discovery Prefix' field containing 'homeassistant'. At the bottom, there is a 'Save' button with a floppy disk icon.

Zigbee Hub mode has the ability to connect to local or remote MQTT brokers. Currently only TCP connections are supported.

This document describes MQTT API for SLZB-OS 3.0.9 or higher

Topics are divided into **IN** and **OUT**.

IN - you can send messages to these topics.

OUT - Zigbee Hub sends messages to these topics.

zHub topics format

Data topic (OUT)

General `data` topic format below:

`base topic / data / zigbee device ieee / zigbee endpoint / zigbee cluster / zigbee attribute`

`base topic` - global prefix, so you can have few Zigbee Hubs connected to one broker, you just have to set different base topics.

`data` - static text (topic type)

`zigbee device ieee` - sender IEEE address in HEX format.

`zigbee endpoint` - zigbee endpoint from which this message is coming, DEC format.

`zigbee cluster` - zigbee cluster from which this message is coming, HEX format.

`zigbee attribute` - zigbee attribute from which this message is coming, HEX format.

Data topic example: `zhub/data/a4c1383439bf5cc9/1/0000/0001`

Read topic (IN) (available from v3.3.0)

This topic accepts requests to read attributes of ZigBee devices.

When you send a message to this topic, the coordinator generates and sends a request for the specified attribute to the target ZigBee device. The device must be online to accept the request, so this is usually used for AC-powered devices.

Topic format: `base topic / read / zigbee device ieee / zigbee endpoint / zigbee cluster / zigbee attribute`

`base topic` - global prefix, so you can have few Zigbee Hubs connected to one broker, you just have to set different base topics.

`read` - static text (topic type)

`zigbee device ieee` - sender IEEE address in HEX format.

`zigbee endpoint` - zigbee endpoint from which this message is coming, DEC format.

`zigbee cluster` - zigbee cluster from which this message is coming, HEX format.

`zigbee attribute` - zigbee attribute from which this message is coming, HEX format.

Read topic example: `zhub/read/a4c1383439bf5cc9/1/0006/0000`

payload: `any text`

Attribute update will be sent to `data` topic!

PLEASE NOTE!

You must add any text content to the payload!

Do not send an empty payload to this topic!

An empty payload will only delete this topic (if it exists). The coordinator will not respond to empty payloads.

Command topic (IN)

This topic is intended for sending ZCL commands to a Zigbee device.

General `cmd` topic format below:

`base topic / cmd / zigbee device ieee / zigbee endpoint / zigbee cluster / zigbee command`

`base topic` - global prefix, so you can have few Zigbee Hubs connected to one broker, you just have to set different base topics.

`cmd` - static text (topic type)

`zigbee device ieee` - target zigbee device IEEE address in HEX format.

`zigbee endpoint` - target zigbee device endpoint to which this message is coming, DEC format.

`zigbee cluster` - target zigbee device cluster to which this message is coming, HEX format.

`zigbee command` - zigbee command to send, HEX format.

Some clusters have special handlers for input commands, such as the ON/OFF or Light cluster. You can find their formats below:

ON/OFF cluster payload format for command topic

`ON` - send ON command

`OFF` - send OFF command

Example: `zhub/cmd/a4c1383439bf5cc9/1/0006` payload: `ON`

Will send command to enable relay or light device.

Level control for Light cluster payload format

`0000` command payload is a number in DEC from 1 to 254, the larger the number, the brighter the lamp will be.

Color control cluster payload format

`0007` command payload is a **color** in **HEX** or **RGB** format. For example: `255,29,0` or `#FFFFFF`

`000a` command payload is a **light temperature** in **mired**. For example: 200

Other clusters

If no built-in clusters or ZCN converters has overridden the processing of this command, if the command contains a payload, it must be a HEX string of the following format:

- Bytes without spaces, uppercase, multiple of two. Example: `010203FF`

- Bytes with spaces, uppercase, grouped by two. Example: `01 02 03 FF`

Write topic (IN)

This topic is intended for writing ZigBee device ZCL attributes.

General `write` topic format below:

`base topic` / `write` / `zigbee device ieee` / `zigbee endpoint` / `zigbee cluster` / `zigbee attribute`

`base topic` - global prefix, so you can have few Zigbee Hubs connected to one broker, you just have to set different base topics.

`write` - static text (topic type)

`zigbee device ieee` - target zigbee device IEEE address in HEX format.

`zigbee endpoint` - target zigbee device endpoint to which this message is coming, DEC format.

`zigbee cluster` - target zigbee device cluster to which this message is coming, HEX format.

`zigbee attribute` - target zigbee device attribute to which this message is coming, HEX format.

Cluster 0006, attribute 4003 payload format

Last state - device will remember its state

ON - device will be on after power loss

OFF - device will be off after power loss

Cluster EF00 (Tuya DP) payload format

Please note that the write topic format for Tuya is different!

base topic / write / zigbee device ieee / 1 / ef00 / data point / data type

data point - Tuya data point id. You can read more about it here:

https://www.zigbee2mqtt.io/advanced/support-new-devices/03_find_tuya_data_points.html

data type - a number that represents the type of data being sent.

0 - RAW, 1 - BOOL, 2 - INT, 3 - STRING, 4 - ENUM, 5 - BITMAP

Examples:

topic: zhub/write/a4c138d089d1418c/1/ef00/0018/1

payload: 1

Any other clusters/attributes payload format

Payload should contain **JSON**: {"type": <zigbee data type>, "data":<data to be sent> }

type - a number that represents the type of data being sent.

Zigbee Data Types and Data Type IDs

Data Class	Data Type	Data Type ID
Null	No data Reserved	0x00 0x01—0x07
General Data	8-bit data 16-bit data 24-bit data 32-bit data 40-bit data 48-bit data 56-bit data 64-bit data	0x08 0x09 0x0a 0x0b 0x0c 0x0d 0x0e 0x0f
Logical	Boolean Reserved	0x10 0x11—0x17

Data Class	Data Type	Data Type ID
Bitmap	8-bit data	0x18
	16-bit data	0x19
	24-bit data	0x1a
	32-bit data	0x1b
	40-bit data	0x1c
	48-bit data	0x1d
	56-bit data	0x1e
	64-bit data	0x1f
Unsigned integer	Unsigned 8-bit integer	0x20
	Unsigned 16-bit integer	0x21
	Unsigned 24-bit integer	0x22
	Unsigned 32-bit integer	0x23
	Unsigned 40-bit integer	0x24
	Unsigned 48-bit integer	0x25
	Unsigned 56-bit integer	0x26
	Unsigned 64-bit integer	0x27
Signed integer	Signed 8-bit integer	0x28
	Signed 16-bit integer	0x29
	Signed 24-bit integer	0x2a
	Signed 32-bit integer	0x2b
	Signed 40-bit integer	0x2c
	Signed 48-bit integer	0x2d
	Signed 56-bit integer	0x2e
	Signed 64-bit integer	0x2f
Enumeration	8-bit enumeration	0x30
	16-bit enumeration	0x31
	Reserved	0x32—0x37
Floating point	Semi-precision	0x38
	Single precision	0x39
	Double precision	0x3a
	Reserved	0x3b—0x3f
String	Reserved	0x40
	Octet string	0x41
	Character string	0x42
	Long octet string	0x43
	Long character string	0x44
	Reserved	0x45—0x47
Ordered sequence	Array	0x48
	Reserved	0x49—0x4b
	Structure	0x4c
	Reserved	0x4d—0x4f
Collection	Set	0x50
	Bag	0x51
	Reserved	0x52—0x57
Reserved	-	0x58—0xdf

Data Class	Data Type	Data Type ID
Time	Time of day Date UTC Time Reserved	0xe0 0xe1 0xe2 0xe3—0xe7
Identifier	Cluster ID Attribute ID BACnet ID Reserved	0xe8 0xe9 0xea 0xeb—0xef
Miscellaneous	IEEE Address 128-bit security key Reserved	0xf0 0xf1 0xf2—0xfe
Unknown	Unknown	0xff

`data` - a HEX string of the following format:

- Bytes without spaces, uppercase, multiple of two. Example: `010203FF`
- Bytes with spaces, uppercase, grouped by two. Example: `01 02 03 FF`

Please note that the number of bytes in the payload **strictly** depends on the data type!
For example, if you send data with type 16-bit integer, the number of bytes in the payload should be 2.

Example: `{"type": 33, "data": "0000"}`

33 - is 0x21 converted to DEC

System control topic (IN) (available from v3.3.0)

This topic allows you to control main functions of the Zigbee Hub.

Topic format: `base_topic / system_control`

Payload format: `{"action": "<system control actions>", <additional parameters>}`

Permit join action

Allows you to open a ZigBee network to add new devices.

Payload format: `{"action": "permit_join", "time": <time to open the network in seconds, from 1 to 254>, "addr": <network address of the device on which to open the network. Can be omitted if the network needs to be opened on all devices>}`

Examples:

`{"action": "permit_join", "time": 60}` - open the entire network for 60 seconds

`{"action": "permit_join", "time": 0}` - close network

`{"action": "permit_join", "time": 60, "addr": 64580}` - open the network for 60 seconds only on device with network address 64580 (DEC number, not HEX)

Configure reporting action

Configures reporting for the selected device. If the device is battery-powered, it must be woken up to accept this command.

Payload format: {"action": "configure_reporting", "ieee": <IEEE address of the target device, HEX string>, "ep": <target endpoint, DEC>, "cl": <target cluster, DEC>, "attr": <target attribute, DEC>, "minRep": <minimum time for reporting in seconds, DEC>, "maxRep": <max time for reporting in seconds, DEC>, "dType": <zigbee reporting data type for this attribute, DEC>, "change": <how much the attribute value must change for reporting to occur. Should be omitted for discrete attributes>}

Examples:

```
{"action": "configure_reporting", "ieee": "3425b4fffe12e9e9", "ep": 1, "cl": 6, "attr": 0, "minRep": 1, "maxRep": 3600, "dType": 0}
```

 - configure ON/OFF attribute reporting to minimum 1s and max 3600s report time. "change" field is omitted because it is a discrete attribute.

```
{"action": "configure_reporting", "ieee": "3425b4fffe12e9e9", "ep": 1, "cl": 2820, "attr": 1285, "minRep": 30, "maxRep": 3600, "dType": 33, "change": 200}
```

 - configure RMS Voltage attribute reporting to minimum 1s and max 3600s report time. Reporting will occur no earlier than 30s if the value has changed by 200 or more (2v) or after a 3600s timeout if value does not change.

Binding action

Binds the target device to the coordinator or to another device.

If one device bound to another, the coordinator will stop receiving reports from the bound device cluster.

Payload format: {"action": "binding", "mode": "<binding mode>", "scrIeee": "<IEEE of the device to which the binding request will be sent, HEX string>", "scrEp": <endpoint number that needs to be bound, DEC number>, "scrCl": <cluster number that needs to be bound, DEC number>, <additional parameters>}

To device mode

Binds one device to another.

Payload format: {"action": "binding", "mode": "to_device", "scrIeee": "<IEEE of the device to which the binding request will be sent, HEX string>", "scrEp": <endpoint number that needs to be bound, DEC number>, "scrCl": <cluster number that needs to be bound, DEC number>, "dstEp": <endpoint number **to which** the binding will be done, DEC number>, "dstIeee": "<IEEE device to which binding will be performed, HEX string>"}

Example: {"action": "binding", "mode": "to_device", "scrIeee": "3425b4fffe12e9e9", "scrEp": 1, "scrCl": 6, "dstEp": 1, "dstIeee": "a4c1389ffb198304"} - binding a Zigbee button (ON/OFF cluster) to a Zigbee relay.

To coordinator mode

Binds to the coordinator so that it can receive reports from this cluster.

Zigbee Hub will attempt to bind automatically when interviewing a device, but this does not always work perfectly.

Payload format: {"action": "binding", "mode": "to_device", "scrIeee": "<IEEE of the device to which the binding request will be sent, HEX string>", "scrEp": <endpoint number that needs to be bound, DEC number>, "scrCl": <cluster number that needs to be bound, DEC number>}

Example: {"action": "binding", "mode": "to_coordinator", "scrIeee": "3425b4fffe12e9e9", "scrEp": 1, "scrCl": 6} - binding a Zigbee button (ON/OFF cluster) to the coordinator.

Revision #14

Created 29 October 2025 19:24:54 by Taras

Updated 14 May 2026 06:56:24 by Taras